

PILOTING A PRECISION LANDSCAPE IRRIGATION ADVISORY SYSTEM - NETZERO

The Problems

Billions of gallons of water are used to irrigate aesthetic high-value landscapes Satellite-only irrigation advisory systems (NASA JPL/SAWSE) not precise enough to advise high-value landscapes

A Solution

- Augment the satellite-only advisory systems, with network of local soil moisture, relative humidity, and ambient temperature measurements
- Local sensors improve accuracy and add additional metrics (local temperature and humidity)



Sensor Features

- Developed by OnsetComp
- Measure a variety of parameters (soil moisture, relative humidity, temperature, etc.)
- Operate as networks transmitting data through each other and back to a centralized hub
- The hub connects to a central database through cel networks
- Operates under the sub-gigahertz range to reduce energy consumption
- Solar-powered
- Operate for up to 10 years with minimal intervention

Sensor Placement Automation

- Variety of variables impact maximize connectivity and quality of data
- reduce error associated with random and arbitrary placement
- Reconstruction based on the elevation and location of obstacles within a desired area.
- does not determine locations with 100% accuracy
- Site visits needed to determine final location



ELECTRICAL & COMPUTER ENGINEERING



Chosen Points

UNIVERSITY of WASHINGTON

Sensor Deployment Pilot



- and mounting
- Complete all necessary training to use ladders, shovels, and excavation and return of soil with minimal disruption
- Developed protocol guidebook for final location of sensors and methods of placement and mounting of sensors
- minimal disruptions to existing landscapes
- many hours carefully deploying sensors and testing connectivity

Sensor Data

- Sensor collects data for soil moisture, soil temperature, relative humidity, and ambient temperature
- calculate irrigation needs in conjunction with the satellite system • Local sensors verify and calibrate satellite data



System Layout

- 3 main components: physical sensors, online database, online dashboard
- Data collected by local sensor network and JPL satellite system
- SASWE dashboard calculates irrigation needs for desired locations
- UW Facilities tailor irrigations to optimal levels with dashboard

ADVISERS: FAISAL HOSSAIN (SASWE Research Group, CEE), BRIAN DAVIS (UW FACILITIES), ERICH ROTH (ONSETCOMP) SPONSOR: UNIVERSITY OF WASHINGTON FACILITIES; SUSTAINABILITY, SATELLITES, WATER, AND ENVIRONMENT RESEARCH GROUP; ONSETCOMP









• Final deployment will utilize multi-sensor zones to collect data



Final Dashboard

- Developed by Shahzaib Khan of the SASWE Group
- Takes satellite and local sensor data to visualize irrigation needs
- Will provide UW facilities with method of verifying and monitoring irrigation demand per week

Future Work, References, and Acknowledgments

- Integration of automated sensor placement into the satellite dashboard
- Utilizing Machine Learning to automatically place sensor locations through constraints and number of sensors
- Whole Campus deployment of sensor system.



Final System Planning

• The final system will be scalable to any desired landscape with a cell signal



Faculty: Faisal Hossain

Undergraduate Students: Nathan Holterhoff, Andrew Line, Vincent Kwok



Acknowledgments: Thank you, OnsetComp for their continued support of this project and supply of sensors